

C-profile lengths (according to Dim. B_{Ri}) | Basic version

Bottom clamp attached either inwards or outwards



970.30.SL
970.32.SL

1500				E4.21			
Width index	B_{Ri} [mm]	Part No. attached inwards	Part No. attached outwards	Width index	B_{Ri} [mm]	Part No. attached inwards	Part No. attached outwards
.015	33	Upon request	960.30.125	.030	48	Upon request	960.30.150
.020	38	Upon request	960.30.125	.040	58	960.30.125	960.30.150
.025	43	Upon request	960.30.150	.050	68	960.30.125	960.30.175
.038	56	Upon request	960.30.150	.060	78	960.30.125	960.30.175
.050	68	960.30.125	960.30.175	.070	88	960.30.150	960.30.175
.068	86	960.30.150	960.30.175	.080	98	960.30.150	960.30.200
.080	98	960.30.150	960.30.200	.090	108	960.30.175	960.30.200
.100	118	960.30.175	960.30.225	.100	118	960.30.175	960.30.225
.125	143	960.30.200	960.30.250	.110	128	960.30.175	960.30.225
				.120	138	960.30.200	960.30.225
				.140	158	960.30.225	960.30.250



Seawater resistant aluminium Super-Trough in a RTG-crane. Long travel with igus® E4 system